

Butterfly check valves with counterweight and oil cylinder flanged PN 10



Art. 5011

Flange: UNI EN 1092-2 PN 10

Face to face length: EN 558-1, serie 14. DIN 3202 F4 Installation: horizontal / vertical with down-up flow direction.

APPLICATIONS ° Water supply ° Drinking water ° Irrigation plants ° Reservoirs ° Dams ° Pumping stations Epoxy paiting suitable for drinking water applications.

The butterfly check valves with counterweight and oil cylinder are very reliable as they can regulate the closing time of the valve. These valves are applied in pipelines as non-return device, with flow allowed in one direction only. The butterfly check valves with counterweight are double eccentric type with tilting disc, the counterweight lever will facilitate the antihammer device and the oil cylinder will slow down the closure movement, to reduce any slam with noise. From DN 900 and up, they come with two counterweight levers and two oil cylinders, one on each side of the valve. Epoxy coated inside and outside, the double flanged butterfly valves can be installed in drinking water plants. NBR gasket seals are on the disc and can be replaced without dismantling the valves from the pipeline.

Materials

body - disc	ductile iron GGG50, EN-GJS-500
disc seat ring	NBR + stainless steel 304
O ring	NBR
counterweight and lever	steel + iron
cylinder	steel
hinge pins	stainless steel X 20 CR 13
painting	epoxy 250 mcr min.

Dimensions	DN	L mm.	D mm.	Weight kg.
	200	230	340	71
	250	250	395	96
	300	270	445	103
	350	290	505	147.5
	400	310	565	196.5
	450	330	615	210
	500	350	670	310
	600	390	780	360
	700	430	895	520
	800	470	1015	650
	900	510	1115	910
	1000	550	1230	1200
	1200	630	1455	2000
	1400	710	1675	3210
	1600	790	1915	4820
	1800	870	2115	7000

Pressure	DN	Nominal pressure	Test pressure Mpa		Max working pressure Mpa
	mm	BAR	body	seat	80°C
	200-1800	10	1,5	1,1	1,0